

# BS EN3 Water & Foam Type Fire Extinguisher



PRESSURE EQUIPMENT DIRECTIVE  
APPROVED FIRE EXTINGUISHERS



0038/03

MARINE EQUIPMENT DIRECTIVE  
APPROVED FIRE EXTINGUISHERS



0038/03



CERTIFIED TO BS EN3  
LICENCE NO. KM 57533



Quality  
Endorsed  
Company

ISO 9001  
Certified



- British Standards Institution – BSI approval.
- Foam type is suitable for Class A & B.
- Water type is suitable for Class A.
- Protective plastic lining.
- All handles stainless steel and colour coded for instant recognition.
- High quality and good value.
- ISO 9001 Certified System by QAS Australia.



## TECHNICAL SPECIFICATION

| EXTINGUISHER TYPE       | 6L  | 9L              | 9L              | 9L              | 9L              |
|-------------------------|---|-----------------|-----------------|-----------------|-----------------|
|                         | FOAM                                      | FOAM            | WATER           | FOAM            | WATER           |
|                         | STORE PRESSURE TYPE (NITROGEN PROPELLENT) |                 |                 | CO2 CARTRIDGE   |                 |
| MODEL NO.               | FEX102                                    | FEX103          | FEX101          | FEX112          | FEX111          |
| FIRE RATING             | 8A, 113B                                  | 13A, 183B       | 13A             | 13A, 183B       | 13A             |
| OPERATING TEMPERATURE   | 5°C to 60°C                               |                 |                 |                 |                 |
| OPERATING PRESSURE      | 12 Bar                                    |                 |                 |                 |                 |
| TEST PRESSURE           | 25 Bar                                    |                 |                 |                 |                 |
| HEIGHT                  | 555mm                                     | 625mm           | 625mm           | 630mm           | 630mm           |
| FULL WEIGHT             | 9.2kg                                     | 13.5kg          | 13.5kg          | 14.2kg          | 14.2kg          |
| DISCHARGE TIME          | 50 secs                                   | 65 secs         | 61 secs         | 94 secs         | 89 secs         |
| RANGE OF THROW (approx) | 4 - 5 M                                   | 4 - 5 M         | 6 M             | 4 - 5 M         | 6 M             |
| CARTON SIZE mm          | 190 x 210 x 565                           | 200 x 200 x 646 | 200 x 200 x 645 | 200 x 200 x 645 | 200 x 200 x 645 |